

FLIGHT TRIMMING

 \Box If the model climbs at high power and high speed add 1 or 2 (#4) washers under the front of the engine mounts to tilt the back of the engine down a bit more.

LANDING IN HIGH WIND CONDITIONS

☐ Input a few clicks of down trim and keep the power on and the airspeed up by 5 to 10mph.

2015 RADIO CONTROL COMPONENTS

USING SPEKTRUM EQUIPMENT

CONTROLS	QTY	SERVO TYPE
Ailerons	2	SPMSA6150
Elevators	1	SPMSA6265
Rudders	2	SPMSA5060
Nana Otanaia	4	000000000
Nose Steering	1	SPMSA6150
Dotroot Valva	1	N/A
Retract Valve	I	IN/A
Flaps	2	SPMSA6150
Ιιαρδ		SF WISAU 130
E-Brake V2	1	SPMSA6265
Receiver	4	2000 4000 4-
Battery	1	3000-4000 mAh

EXTENTION LEADS				
Fuse	Booms	Wing	ALL HD	
2			ALL HD 18"	
		2	12"	
	1		36"	
1			18"	
	2		18"	
	1 (stab)		18" 24" 12"	
2			12"	
2			18"	
		2	6"	
			N/A	

JR Heavy Duty servo arm to be used on elevator (comes standard with 6260 servo).

Optional: JR "MatchMaker" (#JRPA915) is very handy, for Bench set-up.

BVM is synonymous with "Success Jets." It is very important to us that you are successful with our products. This extensive manual reflects our sincerity. As always, your comments and suggestions on BVM products are appreciated.

BVM © 2015 63 05/11/2015